

# Double Roman



Double Roman Terracotta Red

## Fittings and accessories

**Tile fittings:** - Cloaked verge tiles (LH & RH)  
- Half tiles

**Ridges:** - Half round  
- Segmental

**Mono ridges:** - Half round

**Hips:** - Half round  
- Segmental

**Valleys:** - Lead, Fibreglass

**Clips:** - Tile, Eaves, Verge

## Roofing systems

**Dry roof systems:** - Ridge, Hip  
- Verge

**Ventilation systems:** - Ridge  
- Eaves  
- Top abutment  
- Tile vent\*  
- Gas terminals

\* Concealed tile vent min. pitch 22.5°

A long established Roman design popular in most regions, ideal for both new build and refurbishment.

**Tile fixing:** Download zonal fixing table from [www.sandtoft.com](http://www.sandtoft.com). Alternatively, use our Fixing SPEC service by completing your details online or calling 0844 9395 999.

## Technical data

Minimum roof pitch*	17.5° Smoothfaced at 100 mm headlap 22.5° Smoothfaced at 75 mm headlap 30° Sandfaced at 75 mm headlap
Headlap (minimum)	75 mm
Headlap (maximum)	120 mm
Batten spacing at max. gauge	345 mm
Batten spacing at min. gauge	300 mm
Size of tile	420 x 334 mm
Covering capacity at max. gauge	10.4 tiles per m <sup>2</sup> (at 100 mm headlap) 9.7 tiles per m <sup>2</sup> (at 75 mm headlap)
Cover width	300 mm
Profile depth	50 mm
Hanging length	398 mm
Weight as laid	46.8 kg per m <sup>2</sup> (at 100 mm headlap) 43.7 kg per m <sup>2</sup> (at 75 mm headlap)
Weight per 1000	4.5 tonnes
Weight per tile	4.5 kg
Weight per pallet (inc. pallet)	1.0 tonnes
Quantity per pallet	228
Battens per m <sup>2</sup>	2.91 m
Batten size	
Up to 450 mm rafter centres	38 x 25 mm
Up to 600 mm rafter centres	50 x 25 mm
Nail size/type for tiles	65 x 3.75 mm aluminium clout head
Nail size/type for tile clips	50 x 3.35 mm aluminium clout head
BRE Green Guide rating	A+


Note: Unless otherwise stated, data is based on tiles laid at minimum headlap.

\* Rafter length restrictions apply at minimum roof pitch.

## Colours Sandfaced



02 Antique No. 2



03 Mottled Red



05 Cornish Grey

## Smoothfaced



10 Brown



11 Terracotta Red



12 Rustic



14 Dark Grey

**Enquiries:** Contact Customer Support on 0844 9395 900 or visit our website at [www.sandtoft.com](http://www.sandtoft.com)

**Sandtoft** 