

# Plain Tile



Plain Tile Rustic

## Fittings and accessories

|                       |  |
|-----------------------|--|
| <b>Tile fittings:</b> | - Tile-and-a-half tiles<br>- Eaves/tops tiles<br>- Cloaked verge tiles (LH & RH)<br>- External & internal angles (LH & RH) |
|-----------------------|--|

|                      |        |
|----------------------|--------|
| <b>Feature tiles</b> | - Club |
|----------------------|--------|

|                |                             |
|----------------|-----------------------------|
| <b>Ridges:</b> | - Half round<br>- Segmental |
|----------------|-----------------------------|

|                     |              |
|---------------------|--------------|
| <b>Mono ridges:</b> | - Half round |
|---------------------|--------------|

|              |  |
|--------------|--|
| <b>Hips:</b> | - Bonnet<br>- Arris<br>- Half round<br>- Segmental |
|--------------|--|

|                 |  |
|-----------------|--|
| <b>Valleys:</b> | - Valley tiles<br>- Lead<br>- Fibreglass |
|-----------------|--|

## Roofing systems

|                          |              |
|--------------------------|--------------|
| <b>Dry roof systems:</b> | - Ridge, Hip |
|--------------------------|--------------|

|                             |  |
|-----------------------------|--|
| <b>Ventilation systems:</b> | - Ridge<br>- Eaves<br>- Top abutment<br>- Tile vent<br>- Gas terminals |
|-----------------------------|--|

This versatile cross-cambered concrete tile is perfect for complex detailing and curved roof applications.

**Tile fixing:** Tiles must be securely fixed to resist wind uplift. Use our Fixing SPEC service by completing your details online or calling 0844 9395 999.

| Technical data                  | Roof                              | Vertical                      |
|---------------------------------|-----------------------------------|-------------------------------|
| Minimum roof pitch              | 35°                               | 75°                           |
| Headlap (minimum)               | 65 mm                             | 38 mm                         |
| Batten spacing at max. gauge    | 100 mm                            | 114 mm                        |
| Size of tile                    | 265 x 165 mm                      | 265 x 165 mm                  |
| Covering capacity at max. gauge | 60.0 tiles per m <sup>2</sup>     | 53.0 tiles per m <sup>2</sup> |
| Cover width                     | 165 mm                            | 165 mm                        |
| Profile depth                   | 13 mm                             | 13 mm                         |
| Hanging length                  | 245 mm                            | 245 mm                        |
| Weight as laid                  | 78.0 kg per m <sup>2</sup>        | 68.9 kg per m <sup>2</sup>    |
| Weight per 1000                 | 1.3 tonnes                        | 1.3 tonnes                    |
| Weight per tile                 | 1.3 kg                            | 1.3 kg                        |
| Weight per pallet (inc. pallet) | 1.0 tonnes                        | 1.0 tonnes                    |
| Quantity per pallet             | 768                               | 768                           |
| Battens per m <sup>2</sup>      | 10 m                              | 8.7 m                         |
| Batten size                     |                                   |                               |
| Up to 450 mm rafter centres     | 38 x 25 mm                        | 38 x 25 mm                    |
| Up to 600 mm rafter centres     | 38 x 25 mm                        | 38 x 25 mm                    |
| Nail size/type for tiles        | 38 x 3.35 mm aluminium clout head |                               |
| Nail size/type for tile clips   | N/A                               |                               |
| BRE Green Guide rating          | A+                                |                               |

Note: Unless otherwise stated, data is based on tiles laid at minimum headlap.

**Feature Tile**  
Club pattern available.



## Colours Sandfaced



## Smoothfaced



**Enquiries:** Contact Customer Support on 0844 9395 900 or visit our website at [www.sandtoft.com](http://www.sandtoft.com)



▲ Lead times apply